


# YARRA



2024-25  
Collection

[www.yarratiles.com](http://www.yarratiles.com)



# About Us

# YARRA

At YARRA Tiles, we believe that every space deserves to be a masterpiece of elegance and beauty. With a proud legacy of 40 years in the building materials business, we are a third-generation enterprise dedicated to redefining the world of tiles. Our passion for innovation, unwavering commitment to quality, and strong ties to nature have made us a revolutionary name in the industry.

[www.yarratiles.com](http://www.yarratiles.com)



# INNOVATION WITH NATURE

Experience the calmness and elegance of nature from the comfort of your own home. Discover the strength, textures, and tones that wood has to offer. The collection of 200x1200mm tiles is everything different you were looking for.



**-BIANCO-**

**-GREY-**

**-MEHOGANY-**

**-MOKA-**

**-TEAK-**

**200X  
1200MM**

**RANDOM**

**8**

**200X  
1200MM**

**RANDOM**

**8**

**200X  
1200MM**

**RANDOM**

**8**

**200X  
1200MM**

**RANDOM**

**8**

**200X  
1200MM**


**RANDOM**

**8**

# YARRA

## MOOD SPACES

The emotion that only handmade things can offer blends with love for materials, respect for traditions and the continuous improvement resulting from masterful daily gestures. In the world of Arthis, past, present and future blend in a material that is full of life to offer a feeling of inspired contemporary craftsmanship to residential and commercial spaces.



# BALBOA BIANCO

YARRA



200X  
1200MM

RANDOM  
10



PHASE - 1



PHASE - 2



PHASE - 3



PHASE - 4



PHASE - 5

PHASE - 6



PHASE - 7



PHASE - 8



PHASE - 9



PHASE - 10



# BALBOA BIANCO





# BALBOA GREY

YARRA



200X  
1200MM

RANDOM  
10



PHASE - 1



PHASE - 2



PHASE - 3



PHASE - 4



PHASE - 5

PHASE - 6



PHASE - 7



PHASE - 8



PHASE - 9



PHASE - 10



# BALBOA MEHOGANY

YARRA



200X  
1200MM

RANDOM  
10



PHASE - 1



PHASE - 2



PHASE - 3



PHASE - 4



PHASE - 5

PHASE - 6



PHASE - 7



PHASE - 8



PHASE - 9



PHASE - 10



# BALBOA TEAK

YARRA




200X  
1200MM

RANDOM  
10



PHASE - 1



PHASE - 2



PHASE - 3



PHASE - 4



PHASE - 5


PHASE - 6



PHASE - 7



PHASE - 8



PHASE - 9



PHASE - 10



# BALBOA TEAK




# BALBOA MOKA

YARRA



200X  
1200MM

RANDOM  
10



PHASE - 1



PHASE - 2



PHASE - 3



PHASE - 4



PHASE - 5

PHASE - 6



PHASE - 7



PHASE - 8



PHASE - 9



PHASE - 10






# BALBOA MOKA



## LAYING SOLUTIONS




The material should be carefully checked before fixing, especially tonality, caliber and choice. Claims cannot be accepted once the material is installed. The company declines all responsibility for laying without joints; minimum joint laying has a gap of 2 mm.

### Porcelain stoneware - Standard EN 14411 (ISO 13006) Annex G Group BIa, E ≤ 0.5%

TECHNICAL SPECIFICATIONS		STANDARDS	VALUES REQUIRED	OUR VALUES	
			RECTIFIED	MATT	
DIMENSIONS		Length and width	± 0,3%, max 1 mm	In According	
		Thickness	± 5%, max 0,5 mm	In According	
		Wedging	± 0,3%, max 1,5 mm	In According	
		Straightness of the edges	± 0,3%, max 0,8 mm	In According	
		Flatness	± 0,4%, max 1,8 mm	In According	
STRUCTURE		Water absorption - average value %	ISO 10545-3	≤ 0,5%	In According
		Breaking strength	ISO 10545-4	S ≥ 1300 N	S ≥ 2000 N
		Modulus of rupture		R ≥ 35 N/mm <sup>2</sup>	In According
		Resistance to surface abrasion	ISO 10545-7	According to classification indicator by manufacture	PEI IV
THERMAL SHOCK		Coefficient of thermal linear expansion	ISO 10545-8	9 x 10 <sup>-6</sup> max	In According
		Thermal shock resistance	ISO 10545-9	Resistant	Resistant
		Resistance to frost	ISO 10545-12	Resistant	Resistant
SAFETY		Dynamic friction coefficient	DIN 51130	According to the space or the working area	R9 / R11
CHEMICAL RESISTANCE		Resistance to high concentrations of acids and alkalis	ISO 10545-13	Class GHC Min.	Class GHA
		Resistance to low concentrations of acids and alkalis		Class GLC Min.	Class GLA
		Stain resistance	ISO 10545-14	Min. class 3	5




## INSTALLATION ADVICE



The longest side should be staggered no more than 300mm when laid in running bond.

## V SHADES



The V-Shade classification indicates the level of shading of the product, ranked from V0 to V4.

## PACKAGING

SIZE	THICKNESS	PCS./BOX	SQM/BOX	SQF/BOX
200x1200 mm	9 MM	5	1.20	12.91

## FEATURES



\*We need minimum 2000sq/mtr order for R11 surface

# YARRA

A Marble Mart Company.  
Asola Farm Rd, Asola Homes, Asola,  
New Delhi, Delhi 110074  
**Contact : 9911097882**

[www.yarratiles.com](http://www.yarratiles.com)  
[yarratiles@gmail.com](mailto:yarratiles@gmail.com)